

Silicon Nitride Ceramic Angular Contact Ball Bearings



パート 番号	盾の種 類	ID	OD	Width	ボール 素材	動的負 荷	静的荷 重	最大 速度(X 1K pm)	Construction	Lubrication	温度範 囲	Precision	Clearance	ROHS	Brand
CE3216	Open	80 mm	140 mm	44.4 mm	Silicon Nitrpide Ceramic	5361.75 lbf	4805.25 lbf	3.24	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3315	Sealed	75 mm	160 mm	68.3 mm	Silicon Nitrpide Ceramic	8902.5 lbf	7081.5 lbf	3.1	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3315	Open	75 mm	160 mm	68.3 mm	Silicon Nitrpide Ceramic	8902.5 lbf	7081.5 lbf	3.1	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3215	Sealed	75 mm	130 mm	41.3 mm	Silicon Nitrpide Ceramic	4835.75 lbf	4451.25 lbf	3.46	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3215	Open	75 mm	130 mm	41.3 mm	Silicon Nitrpide Ceramic	4835.75 lbf	4451.25 lbf	3.46	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3314	Sealed	70 mm	150 mm	63.5 mm	Silicon Nitrpide Ceramic	8244.75 lbf	6322.75 lbf	3.24	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3314	Open	70 mm	150 mm	63.5 mm	Silicon Nitrpide Ceramic	8244.75 lbf	6322.75 lbf	3.24	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3214	Sealed	70 mm	125 mm	39.7 mm	Silicon Nitrpide Ceramic	4471.5 lbf	4046.5 lbf	3.6	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3214	Open	70 mm	125 mm	39.7 mm	Silicon Nitrpide Ceramic	4471.5 lbf	4046.5 lbf	3.6	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3313	Sealed	65 mm	140 mm	58.7 mm	Silicon Nitrpide Ceramic	7385 lbf	5564 lbf	3.46	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3313	Open	65 mm	140 mm	58.7 mm	Silicon Nitrpide Ceramic	7385 lbf	5564 lbf	3.46	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3213	Sealed	65 mm	120 mm	38.1 mm	Silicon Nitrpide Ceramic	4077 lbf	3717.75 lbf	3.82	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3213	Open	65 mm	120 mm	38.1 mm	Silicon Nitrpide Ceramic	4077 lbf	3717.75 lbf	3.82	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3312	Sealed	60 mm	130 mm	54 mm	Silicon Nitrpide Ceramic	6424 lbf	4805.25 lbf	3.82	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3312	Open	60 mm	130 mm	54 mm	Silicon Nitrpide Ceramic	6424 lbf	4805.25 lbf	3.82	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3212	Sealed	60 mm	110 mm	36.5 mm	Silicon Nitrpide Ceramic	3793.75 lbf	3237.25 lbf	4.03	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG

Silicon Nitride Ceramic Angular Contact Ball Bearings

CE3212	Open	60 mm	110 mm	36.5 mm	Silicon Nitride Ceramic	3793.75 lbf	3237.25 lbf	4.03	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3311	Sealed	55 mm	120 mm	49.2 mm	Silicon Nitride Ceramic	5665.25 lbf	4122.5 lbf	4.03	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3311	Open	55 mm	120 mm	49.2 mm	Silicon Nitride Ceramic	5665.25 lbf	4122.5 lbf	4.03	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3211	Sealed	55 mm	100 mm	33.3 mm	Silicon Nitride Ceramic	3085.5 lbf	2630.25 lbf	4.54	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3211	Open	55 mm	100 mm	33.3 mm	Silicon Nitride Ceramic	3085.5 lbf	2630.25 lbf	4.54	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3310	Sealed	50 mm	110 mm	44.4 mm	Silicon Nitride Ceramic	4805.25 lbf	3515.5 lbf	4.32	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3310	Open	50 mm	110 mm	44.4 mm	Silicon Nitride Ceramic	4805.25 lbf	3515.5 lbf	4.32	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3210	Sealed	50 mm	90 mm	30.2 mm	Silicon Nitride Ceramic	2579.75 lbf	2149.75 lbf	5.11	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3210	Open	50 mm	90 mm	30.2 mm	Silicon Nitride Ceramic	2579.75 lbf	2149.75 lbf	5.11	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3309	Sealed	45 mm	100 mm	39.7 mm	Silicon Nitride Ceramic	3793.75 lbf	2680.75 lbf	4.82	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3309	Open	45 mm	100 mm	39.7 mm	Silicon Nitride Ceramic	3793.75 lbf	2680.75 lbf	4.82	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3209	Sealed	45 mm	85 mm	30.2 mm	Silicon Nitride Ceramic	2630.25 lbf	2099.25 lbf	5.54	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3209	Open	45 mm	85 mm	30.2 mm	Silicon Nitride Ceramic	2630.25 lbf	2099.25 lbf	5.54	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG
CE3308	Sealed	40 mm	90 mm	36.5 mm	Silicon Nitride Ceramic	3313 lbf	2428 lbf	5.4	Double Row	Dry	□176 to 1472°F	ABEC-1	C0	Compliant	XZBRG