

Zirconia Ceramic Angular Contact Ball Bearings



パート 番号	盾の種 類	ID	OD	Width	ボール 素材	動的負 荷	静的荷 重	最大 速度(X 1K pm)	Construction	Lubrication	温度 範囲	Precision	Clearance	ROHS	Brand
CE3216	Open	80 mm	140 mm	44.4 mm	Zirconia Ceramic	6434.1 lbf	5766.3 lbf	2.83	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3315	Sealed	75 mm	160 mm	68.3 mm	Zirconia Ceramic	10683 lbf	8497.8 lbf	2.71	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3315	Open	75 mm	160 mm	68.3 mm	Zirconia Ceramic	10683 lbf	8497.8 lbf	2.71	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3215	Sealed	75 mm	130 mm	41.3 mm	Zirconia Ceramic	5802.9 lbf	5341.5 lbf	3.02	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3215	Open	75 mm	130 mm	41.3 mm	Zirconia Ceramic	5802.9 lbf	5341.5 lbf	3.02	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3314	Sealed	70 mm	150 mm	63.5 mm	Zirconia Ceramic	9893.7 lbf	7587.3 lbf	2.83	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3314	Open	70 mm	150 mm	63.5 mm	Zirconia Ceramic	9893.7 lbf	7587.3 lbf	2.83	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3214	Sealed	70 mm	125 mm	39.7 mm	Zirconia Ceramic	5365.8 lbf	4855.8 lbf	3.15	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3214	Open	70 mm	125 mm	39.7 mm	Zirconia Ceramic	5365.8 lbf	4855.8 lbf	3.15	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3313	Sealed	65 mm	140 mm	58.7 mm	Zirconia Ceramic	8862 lbf	6676.8 lbf	3.02	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3313	Open	65 mm	140 mm	58.7 mm	Zirconia Ceramic	8862 lbf	6676.8 lbf	3.02	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3213	Sealed	65 mm	120 mm	38.1 mm	Zirconia Ceramic	4892.4 lbf	4461.3 lbf	3.34	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG

Zirconia Ceramic Angular Contact Ball Bearings

CE3213	Open	65 mm	120 mm	38.1 mm	Zirconia Ceramic	4892.4 lbf	4461.3 lbf	3.34	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3312	Sealed	60 mm	130 mm	54 mm	Zirconia Ceramic	7708.8 lbf	5766.3 lbf	3.34	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3312	Open	60 mm	130 mm	54 mm	Zirconia Ceramic	7708.8 lbf	5766.3 lbf	3.34	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3212	Sealed	60 mm	110 mm	36.5 mm	Zirconia Ceramic	4552.5 lbf	3884.7 lbf	3.53	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3212	Open	60 mm	110 mm	36.5 mm	Zirconia Ceramic	4552.5 lbf	3884.7 lbf	3.53	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3311	Sealed	55 mm	120 mm	49.2 mm	Zirconia Ceramic	6798.3 lbf	4947 lbf	3.53	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3311	Open	55 mm	120 mm	49.2 mm	Zirconia Ceramic	6798.3 lbf	4947 lbf	3.53	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3211	Sealed	55 mm	100 mm	33.3 mm	Zirconia Ceramic	3702.6 lbf	3156.3 lbf	3.97	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3211	Open	55 mm	100 mm	33.3 mm	Zirconia Ceramic	3702.6 lbf	3156.3 lbf	3.97	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3310	Sealed	50 mm	110 mm	44.4 mm	Zirconia Ceramic	5766.3 lbf	4218.6 lbf	3.78	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3310	Open	50 mm	110 mm	44.4 mm	Zirconia Ceramic	5766.3 lbf	4218.6 lbf	3.78	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3210	Sealed	50 mm	90 mm	30.2 mm	Zirconia Ceramic	3095.7 lbf	2579.7 lbf	4.47	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3210	Open	50 mm	90 mm	30.2 mm	Zirconia Ceramic	3095.7 lbf	2579.7 lbf	4.47	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3309	Sealed	45 mm	100 mm	39.7 mm	Zirconia Ceramic	4552.5 lbf	3216.9 lbf	4.22	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3309	Open	45 mm	100 mm	39.7 mm	Zirconia Ceramic	4552.5 lbf	3216.9 lbf	4.22	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3209	Sealed	45 mm	85 mm	30.2 mm	Zirconia Ceramic	3156.3 lbf	2519.1 lbf	4.85	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3209	Open	45 mm	85 mm	30.2 mm	Zirconia Ceramic	3156.3 lbf	2519.1 lbf	4.85	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG
CE3308	Sealed	40 mm	90 mm	36.5 mm	Zirconia Ceramic	3975.6 lbf	2913.6 lbf	4.73	Double Row	Dry	□176 to 752 °F	ABEC-1	C0	Compliant	XZBRG