

# AISI440C



| 製品番号          | シールの種類   | ボア<br>ディ<br>ア | アウト<br>ター<br>ディ<br>ア | Width    | 動的<br>放射<br>荷重 | 静的<br>放射<br>荷重 | 最高速<br>度(X1000rpm) | Material | ケー<br>ジ素<br>材       | 精密等<br>級 | Clearance | ROHS      | SGS       |
|---------------|----------|---------------|----------------------|----------|----------------|----------------|--------------------|----------|---------------------|----------|-----------|-----------|-----------|
| S62200<br>2rs | Sealed   | 10<br>mm      | 30<br>mm             | 14<br>mm | 5400<br>N      | 2160<br>N      | 26.1               | 440C     | 440C<br>or<br>Nylon | ABEC-1   | C0        | Compliant | Compliant |
| S6200zz       | Shielded | 10<br>mm      | 30<br>mm             | 9 mm     | 4590<br>N      | 2160<br>N      | 21.6               | 440C     | 440C<br>or<br>Nylon | ABEC-1   | C0        | Compliant | Compliant |
| S6200 2rs     | Sealed   | 10<br>mm      | 30<br>mm             | 9 mm     | 4590<br>N      | 2160<br>N      | 21.6               | 440C     | 440C<br>or<br>Nylon | ABEC-1   | C0        | Compliant | Compliant |
| S6200         | Open     | 10<br>mm      | 30<br>mm             | 9 mm     | 4590<br>N      | 2160<br>N      | 21.6               | 440C     | 440C<br>or<br>Nylon | ABEC-1   | C0        | Compliant | Compliant |
| S6000zz       | Shielded | 10<br>mm      | 26<br>mm             | 8 mm     | 4095<br>N      | 1755<br>N      | 27.9               | 440C     | 440C<br>or<br>Nylon | ABEC-1   | C0        | Compliant | Compliant |
| S6000 2rs     | Sealed   | 10<br>mm      | 26<br>mm             | 8 mm     | 4095<br>N      | 1755<br>N      | 27.9               | 440C     | 440C<br>or<br>Nylon | ABEC-1   | C0        | Compliant | Compliant |
| S6000         | Open     | 10<br>mm      | 26<br>mm             | 8 mm     | 4095<br>N      | 1755<br>N      | 27.9               | 440C     | 440C<br>or<br>Nylon | ABEC-1   | C0        | Compliant | Compliant |
| S16100zz      | Shielded | 10<br>mm      | 28<br>mm             | 8 mm     | 4140<br>N      | 1800<br>N      | 22.5               | 440C     | 440C<br>or<br>Nylon | ABEC-1   | C0        | Compliant | Compliant |
| S16100        | Open     | 10<br>mm      | 28<br>mm             | 8 mm     | 4140<br>N      | 1800<br>N      | 22.5               | 440C     | 440C<br>or<br>Nylon | ABEC-1   | C0        | Compliant | Compliant |
| S699zz        | Shielded | 9<br>mm       | 20<br>mm             | 6 mm     | 1887<br>N      | 778<br>N       | 30.6               | 440C     | 440C<br>or<br>Nylon | ABEC-1   | C0        | Compliant | Compliant |
| S699 2rs      | Sealed   | 9<br>mm       | 20<br>mm             | 6 mm     | 1887<br>N      | 778<br>N       | 30.6               | 440C     | 440C<br>or<br>Nylon | ABEC-1   | C0        | Compliant | Compliant |
| S699          | Open     | 9<br>mm       | 20<br>mm             | 6 mm     | 1887<br>N      | 778<br>N       | 30.6               | 440C     | 440C<br>or<br>Nylon | ABEC-1   | C0        | Compliant | Compliant |
| S689zz        | Shielded | 9<br>mm       | 17<br>mm             | 5 mm     | 1015<br>N      | 481<br>N       | 32.4               | 440C     | 440C<br>or<br>Nylon | ABEC-1   | C0        | Compliant | Compliant |
| S689 2rs      | Sealed   | 9<br>mm       | 17<br>mm             | 5 mm     | 1015<br>N      | 481<br>N       | 32.4               | 440C     | 440C<br>or<br>Nylon | ABEC-1   | C0        | Compliant | Compliant |

## AISI440C

|            |          |      |       |        |        |        |      |      |               |        |    |           |           |
|------------|----------|------|-------|--------|--------|--------|------|------|---------------|--------|----|-----------|-----------|
| S689       | Open     | 9 mm | 17 mm | 4 mm   | 1015 N | 481 N  | 32.4 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |
| S679zz     | Shielded | 9 mm | 14 mm | 4.5 mm | 703 N  | 337 N  | 32.4 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |
| S679 2rs   | Sealed   | 9 mm | 14 mm | 4.5 mm | 703 N  | 337 N  | 32.4 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |
| S679       | Open     | 9 mm | 14 mm | 3 mm   | 703 N  | 337 N  | 32.4 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |
| S639zz     | Shielded | 9 mm | 30 mm | 10 mm  | 3564 N | 1498 N | 21.6 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |
| S639 2rs   | Sealed   | 9 mm | 30 mm | 10 mm  | 3564 N | 1498 N | 21.6 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |
| S639       | Open     | 9 mm | 30 mm | 10 mm  | 3564 N | 1498 N | 21.6 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |
| S629zz     | Shielded | 9 mm | 26 mm | 8 mm   | 3491 N | 1427 N | 25.2 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |
| S629 2rs   | Sealed   | 9 mm | 26 mm | 8 mm   | 3491 N | 1427 N | 25.2 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |
| S629       | Open     | 9 mm | 26 mm | 8 mm   | 3491 N | 1427 N | 25.2 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |
| S609zz     | Shielded | 9 mm | 24 mm | 7 mm   | 2568 N | 1040 N | 28.8 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |
| S609 2rs   | Sealed   | 9 mm | 24 mm | 7 mm   | 2568 N | 1040 N | 28.8 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |
| S609       | Open     | 9 mm | 24 mm | 7 mm   | 2568 N | 1040 N | 28.8 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |
| SMR148zz   | Shielded | 8 mm | 14 mm | 4 mm   | 626 N  | 278 N  | 34.2 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |
| SMR148 2rs | Sealed   | 8 mm | 14 mm | 4 mm   | 626 N  | 278 N  | 34.2 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |
| SMR148     | Open     | 8 mm | 14 mm | 3.5 mm | 626 N  | 278 N  | 34.2 | 440C | 440C or Nylon | ABEC-1 | C0 | Compliant | Compliant |