

SGE..C SERIES



パート 番号	d	D1	B	c	dk	rs	r1s	Dynamic	Static	$\alpha^\circ \approx$	重量 kg	計測シ ステム	Material	温度 範囲	RoHS	ISO: 9001	ラジアル クリアラ ンス
Sge8c	8	16	8	5	13	0.3	0.3	5.8	14	15	0.008	Metric	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sge6c	6	14	6	4	10	0.3	0.3	3.6	9.1	13	0.004	Metric	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sge4c	4	12	5	3	8	0.3	0.3	2.1	5.4	16	0.003	Metric	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sge5c	5	14	6	4	10	0.3	0.3	3.6	9.1	13	0.005	Metric	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sge30c	30	47	22	18	40.7	0.6	0.3	65	166	6	0.163	Metric	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sge25c	25	42	20	16	35.5	0.6	0.3	51	127	7	0.119	Metric	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sge20c	20	35	16	12	29	0.3	0.3	31	78	9	0.066	Metric	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sge17c	17	30	14	10	25	0.3	0.3	22	56	10	0.041	Metric	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sge15c	15	26	12	9	22	0.3	0.3	18	45	8	0.027	Metric	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sge12c	12	22	10	7	18	0.3	0.3	11	28	10	0.015	Metric	Steel	-20° to 80° C	Compliant	Compliant	Standard
Sge10c	10	19	9	6	16	0.3	0.3	8.6	21	12	0.011	Metric	Steel	-20° to 80° C	Compliant	Compliant	Standard