

SPOS SERIES



パート 番号	ID	ボール 幅B	ハウ スリ ング 幅C	ヘッド 径A	ボール センタ h1 までの 長さ	部 品 長 L4	ね じ 長	ネジサイ ズ 6H	ボール ・ ディ ア m	傾 斜 角 度	重 量	計測シ ステム	Material	温度 範囲	RoHS	ISO: 9001	ラジアル クリアラ ンス
Spos22	22	28	20	54	84	111	48	M22x1.5	38.1	15	433	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Spos20	20	25	18	50	78	103	45	M20x1.5	34.9	14	325	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Spos18	18	23	16.5	46	72	95	41	M18x1.5	31.8	15	255	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Spos16	16	21	15	42	66	87	37	M16	28.6	15	189	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Spos14	14	19	13.5	36	60	78	36	M14	25.4	16	124	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Spos12	12	16	12	32	54	70	32	M12	22.2	13	60	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Spos10	10	14	10.5	28	48	62	28	M10	19.1	13	55	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Spos25	25	31	22	60	94	124	55	M24x2	42.9	15	580	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Spos28	28	35	24	66	103	136	62	M27x2	47.6	15	714	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Spos30	30	37	25	70	110	145	66	M30x2	50.8	17	963	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard

SPOS SERIES

Spos5	5	8	6	18	33	42	19	M5	11.1	13	14	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Spos6	6	9	6.75	20	36	46	21	M6	12.7	13	18	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Spos8	8	12	9	24	42	54	25	M8	15.9	14	33	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard