

Stainless Miniature Flanged Ball Bearings



パート番号	ID	OD	Width	フランジ外線	フランジ幅	盾の種類	動的負荷	静的荷重	最高速度(X1000rpm)	リング素材	計測システム	ベアリングタイプ	ボールベアリングタイプ	精密評価	Clearance	温度範囲	RoHS	SGS
SMF115	5 mm	11 mm	4 mm	12.6 mm	0.8 mm	Open	123 lbf	46 lbf	40.5	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF105zz	5 mm	10 mm	4 mm	11.6 mm	0.8 mm	Shielded	74 lbf	27 lbf	45	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF105 2rs	5 mm	10 mm	4 mm	11.6 mm	0.8 mm	Sealed	74 lbf	27 lbf	45	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF105	5 mm	10 mm	3 mm	11.2 mm	0.6 mm	Open	74 lbf	27 lbf	45	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF695zz	5 mm	13 mm	4 mm	15 mm	1 mm	Shielded	185 lbf	70 lbf	38.7	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF695 2rs	5 mm	13 mm	4 mm	15 mm	1 mm	Sealed	185 lbf	70 lbf	38.7	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF695	5 mm	13 mm	4 mm	15 mm	1 mm	Open	185 lbf	70 lbf	38.7	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF685zz	5 mm	11 mm	5 mm	12.5 mm	1 mm	Shielded	123 lbf	46 lbf	40.5	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF685 2rs	5 mm	11 mm	5 mm	12.5 mm	1 mm	Sealed	123 lbf	46 lbf	40.5	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF685	5 mm	11 mm	3 mm	12.5 mm	0.8 mm	Open	123 lbf	46 lbf	40.5	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF635zz	5 mm	19 mm	6 mm	22 mm	1.5 mm	Shielded	402 lbf	145 lbf	28.8	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF635 2rs	5 mm	19 mm	6 mm	22 mm	1.5 mm	Sealed	402 lbf	145 lbf	28.8	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF635	5 mm	19 mm	6 mm	22 mm	1.5 mm	Open	402 lbf	145 lbf	28.8	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF625zz	5 mm	16 mm	5 mm	18 mm	1 mm	Shielded	297 lbf	109 lbf	32.4	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF625 2rs	5 mm	16 mm	5 mm	18 mm	1 mm	Sealed	297 lbf	109 lbf	32.4	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF625	5 mm	16 mm	5 mm	18 mm	1 mm	Open	297 lbf	109 lbf	32.4	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant

Stainless Miniature Flanged Ball Bearings

SF605zz	5 mm	14 mm	5 mm	16 mm	1 mm	Shielded	229 lbf	82 lbf	36	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF605 2rs	5 mm	14 mm	5 mm	16 mm	1 mm	Sealed	229 lbf	82 lbf	36	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF605	5 mm	14 mm	5 mm	16 mm	1 mm	Open	229 lbf	82 lbf	36	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF84zz	4 mm	8 mm	3 mm	9.2 mm	0.6 mm	Shielded	68 lbf	23 lbf	50.4	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF84 2rs	4 mm	8 mm	3 mm	9.2 mm	0.6 mm	Sealed	68 lbf	23 lbf	50.4	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF84	4 mm	8 mm	2 mm	9.2 mm	0.6 mm	Open	68 lbf	23 lbf	50.4	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF74zz	4 mm	7 mm	2.5 mm	8.2 mm	0.6 mm	Shielded	44 lbf	17 lbf	54	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF74 2rs	4 mm	7 mm	2.5 mm	8.2 mm	0.6 mm	Sealed	44 lbf	17 lbf	54	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF74	4 mm	7 mm	2 mm	8.2 mm	0.6 mm	Open	54 lbf	19 lbf	54	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF104zz	4 mm	10 mm	4 mm	11.6 mm	0.8 mm	Shielded	122 lbf	44 lbf	43.2	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF104 2rs	4 mm	10 mm	4 mm	11.6 mm	0.8 mm	Sealed	122 lbf	44 lbf	43.2	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SMF104	4 mm	10 mm	3 mm	11.2 mm	0.6 mm	Open	122 lbf	44 lbf	43.2	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF694zz	4 mm	11 mm	4 mm	12.5 mm	1 mm	Shielded	165 lbf	57 lbf	43.2	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SF694 2rs	4 mm	11 mm	4 mm	12.5 mm	1 mm	Sealed	165 lbf	57 lbf	43.2	440C Stainless Steel	Inch	Ball	Flanged	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant